

MOX-TRFH-3741 SERIES



ELECTRICAL SPECIFICATIONS

| MoxiE Part Number | Electrical Specifications | Operating Temperature Range | Test Frequency | DCR (Ω Max.) |
|-------------------|---------------------------|-----------------------------|----------------|------------------------------------|
| MOX-TRFH-3741 | L : (4-3) = 19mH Min. | -25°C TO +105°C | 10KHz / 50mV | (4-3) = 1.280 Ω Max. @ 25°C |
| | L : (8-7) = 240uH Min. | -25°C TO +105°C | 10KHz / 50mV | (8-7) = 16m Ω Max. @ 25°C |
| | L : (2-1) = 30uH Min. | -25°C TO +105°C | 10KHz / 50mV | (5-6) = 49m Ω Max. @ 25°C |
| | L : (5-6) = 30uH Min. | -25°C TO +105°C | 10KHz / 50mV | (2-1) = 49m Ω Max. @ 25°C |

MoxiE Notes:

- RoHS compliant.
- MoxiE Inductor Corporation specifications are subject to change without notice.
- MoxiE Inductor Corporation customer designs available~contact your MoxiE sales representative for details.
- MoxiE Inductor Corporation custom products are subject to United States Copyright and or Patent protection(s).